



## 370 VK TC DUAL

Affettatrice verticale adatta al taglio della carne fresca, compatta per sfruttare al meglio lo spazio disponibile e con grande capacità di taglio.
Il piatto ampio ed il pressamerce importante possono essere facilmente estratti per la pulizia, così come il dispositivo di supporto fette appositamente progettato per tagliare fette anche molto sottili, perfette e senza scarto.

Come tutti i prodotti Kolossal anche la linea DUAL può essere pulita con getto d'acqua.

Vertical slicer qualified to cut fresh meat, compact in order to require limited counter space, and with great cutting capacity. The wide plate and the significant meat press are easily removable to best clean the machine, just as the stub which has been purposely projected to cut very thin and perfect slices without any product waste. As all Kolossal products, also the DUAL range can be cleaned with water jet.











# olossal d

#### 370 VK TC DUAL - Dotazioni di serie

- Trasmissione a ingranaggio o a cinghia
- Affilatoio incorporato e di facile impiego o affilatoio separato per una più facile pulizia
- Grande capacità e precisione di taglio
- Ampio piano di appoggio per il prodotto tagliato
- Altezza di carico ridotta per diminuire la fatica dell'operatore
- Piatto portamerce con pressamerce basculante ed estraibile in alluminio
- Superfici in alluminio lucidato a specchio e accurati canalini di scorrimento, per diminuire gli attriti e semplificare la pulizia
- Compatta per sfruttare al meglio lo spazio disponibile
- Affilatoio, coprilama, parafetta, ceppo, piatto portamerce e pressamerce completamente asportabili per un'accurata pulizia
- Conforme alle Direttive e Regolamenti europei in vigore
- Prodotto certificato MOCA (Materiali e Oggetti a Contatto con Alimenti)

















#### 370 VK TC DUAL - Standard features

- Gear box or belt transmission
- Built-in sharpener easy to use or separate sharpener for easy cleaning
- Great and precise cutting capacity
- Wide frame for the product
- Low loading height to reduce the strain of the operator
- Plate with swinging and removable remnant holder in aluminum
- Ultra smooth, polished aluminum surfaces and accurate grooves to reduce friction and simplify cleaning
- Limited counter space required
- Removable sharpener, blade guard, deflector, stub, plate and remnant holder for easy cleaning
- Compliant with current European Directives and Regulations
- FCMs (Food Contact Materials) certified product

### CARATTERISTICHE TECNICHE

***************************************	
Diametro lama	370 mm
Velocità lama	230 g/min (cinghia); 200 g/min (ingranaggio)
Spessore fette	da 0 a 24 mm
Corsa carrello	370 mm
Protezione elettrica	IPX3 (Motore IPX5)
Peso netto	55 kg
Caratteristiche elettriche	230 V / 360W a.c. monofase 220-230V, 380-400V / 350W a.c. trifase
Capacità di taglio	Ø 260 mm ☑ 335 x 260 mm

#### TECHNICAL SPECIFICATIONS

TECHNICAL SI ECH ICATIONS	
Blade diameter	370 mm
Blade speed	230 rpm (belt); 200 rpm (gear)
Slice thickness	0 to 24 mm
Carriage travel	370 mm
Electrical protection	IPX3 (Motor IPX5)
Net weight	55 Kg
Electrical specifications	230 V / 360W a.c. monophase 220-230V, 380-400V / 350W a.c. threephase
Cutting capacity	Ø 260 mm  335 x 260 mm

